

BORN OF GREATNESS

FROM THE MAKERS OF HAYABUSA AND GSX-R

GIXXER



GIXXER SF/GIXXER Series Specifications

Engine

Engine Type:	4-Cycle, 1-Cylinder, Air-cooled
Valve System:	SOHC
Displacement:	155 cm ³
Bore x Stroke:	56 mm x 62.9 mm
Max Power:	13.6ps@8000rpm
Max Torque:	13.8Nm@6000rpm
Fuel System:	Fuel Injection
Starter System:	Electric
Transmission Type:	5 Speed, MT

Dimensions and Weight

Overall Length (GIXXER SF):	2025 mm	Wheels:	Cast
Overall Length (GIXXER):	2020 mm	Seat Height:	795 mm
Overall Width (GIXXER SF):	715 mm	Kerb Mass (GIXXER SF):	148 kg
Overall Width (GIXXER):	800 mm	Kerb Mass (GIXXER):	141 kg
Overall Height:	1035 mm	Fuel Tank:	12 L
Wheel Base (GIXXER SF):	1340 mm		
Wheel Base (GIXXER):	1335 mm		
Ground Clearance (GIXXER SF):	165 mm		
Ground Clearance (GIXXER):	160 mm		

Suspension

Front:	Telescopic
Rear:	Swing Arm

Tyre Size

Front:	100/80-17M/C 52P
Rear:	140/60R17M/C 63P

Brake

Front:	Disc
Rear:	Disc

Electrical

Battery:	Maintenance-free, 12V 3Ah
Headlight:	LED
Tail Light:	LED

Regd. Office, Sales & Marketing Office: 2nd Floor, Plot No. 1, Nelson Mandela Road, Vasant Kunj, New Delhi - 110 070. Fax: 011-4607 5418.

Ride safe. Wear a helmet. | Prices of the vehicles are available on our website. Visit us at: www.suzukimotorcycle.co.in /Suzuki2wheelers #amGIXXER /Suzuki2wheelers /Suzuki2wheelers

Specifications, appearances, equipments, colours, materials and other items of the Suzuki product shown in this leaflet are subject to change by the manufacturer at any time without notice and they may vary depending upon local conditions and requirements. Please visit your local dealer for details of any changes. Actual body colour may differ from the colours in this leaflet. *ABS is not designed to shorten the braking distance. ABS cannot prevent wheel skidding caused by braking while cornering. Please ride carefully and do not overly rely on ABS.